

Index

- A**
- Acoustic emission (AE), viii
 - grinding process monitoring, 50
 - RMS fluctuation, 51
 - sensor, viii
 - signals, 51
 - transducer used in applications, viii
 - AE, *see* Acoustic emission
 - AFM, *see* Atomic force microscopy
 - Al-series specimens, 202
 - Analysis of variance (ANOVA), 233
 - Anode effect, 52
 - ANOVA, *see* Analysis of variance
 - Atomic force microscopy (AFM), 98, 132, 157
- B**
- Ball-nose wheels, 45, 46
 - Bonding
 - materials, 8
 - statuses, 217
 - Breakdown voltage, 139
 - Brittle-ductile transition, 68
- C**
- Center-type grinding, 28
 - Ceramics
 - efficient shape-grinding for, 10
 - grinding force for, 9
 - honoring materials, 77
 - Chemical vapor deposition (CVD), 132
 - Chip thickness model, 54
 - Corrosion
 - anodic polarization corrosion test system, 203
 - electrical, prevention of, 78
 - potential, 218, 219
 - rate test, 207
 - resistance
 - evaluation, 207
 - passive state, 221
 - stainless steels, 201
 - test conditions, 207
 - C-series specimens, 202
 - CVD, *see* Chemical vapor deposition
- D**
- Desktop and micro-ELID grinding, 111–122
 - desktop fabrication systems, concept of, 112–113
 - desktop fabrication systems, development of, 113–121
 - desktop lap grinding machine, 115
 - desktop microtool grinding machines, 116–121
 - desktop multiaxes grinding/milling/cutting machines, 115–116
 - desktop surface grinding/slicing machine, 113–114
 - desktop four-axis machine, 116
 - desktop machine concept design, 113
 - desktop machine development, background of, 111
 - desktop slicing for optical glass, 114
 - desktop three-axis machine, 115
 - ELID grinding examples, 117
 - ELID grinding setup, 116
 - examples of microtools ground by two wheels, 121
 - extremely fine microtool, 119
 - grinding machine with ELID unit, 119
 - grinding results of microtool, 119
 - machining examples by microtools, 120
 - microtool grinding principle, 118
 - micro-workshop, 112
 - miniaturization of devices, 111
 - mirror surface by cutting, 118
 - on-machine measuring capability, 112
 - personal computers, 112
 - profile accuracy, 111
 - rotary index table, 116
 - tungsten carbide, 115
- Diamond**
- abrasives, charging of, 149
 - like carbon (DLC), 208, 209
- Dissolved oxygen, 202, 226
- DLC, *see* Diamond-like carbon
- Ductile-mode grinding, vii
- E**
- ED truing, *see* Electrodischarge truing
 - EDX diffraction system, *see* Energy-dispersive x-ray diffraction system
 - Electrode(s)
 - adjusted, 25, 106
 - aspheric grinding, 32
 - coolant flow between, 14
 - copper, 29, 144
 - copper tungsten, 11

- desktop slicing machine. 114
- detail, 4
- double-sided grinding, 70
- drive unit, 76
- ELID polishing, 143
- experimental setup, 31, 52, 142
- fixed, viii, 3
- four-axes ultraprecision machine tool, 96
- freedom grinding, 89
- gap between wheel and, 150, 230
- microtool grinding, 118
- nanoprecision surface finishing, 10
- negative, 38, 47, 53, 62
- paraboloidal lens processing, 102
- positive, 47
- rotary, 162
- rotary grinding system, 27
- selection, 4
- surface modification reactions, 201
- Electrodischarge (ED) truing, 11, 151
- Electrolytic in-process dressing (ELID), vii
 - areas of use, 37
 - centerless grinding, 30
 - cylindrical grinder, 28
 - description, 75
 - desktop machines mounted with, 111
 - electrical behavior, 7
 - electrodes, 25, 105
 - first proposed grinding, vii
 - grinding conditions, 106, 189
 - grinding machine for semiconductor wafer, 126
 - grinding method principle, 3, 4
 - grinding setup, 116
 - large optics produced by, 107–108
 - microlens mold fabrication, 42
 - polishing, experimental setup, 142
 - semiconductors, ix, 124
 - semidry method, 38
 - single-side lap grinding, 61
 - solid immersion mirror, 95
 - system principle, 15
 - ultraprecision mirror surface machining system with ELID, 104
- ELID, *see* Electrolytic in-process dressing
- Energy-dispersive x-ray (EDX) diffraction system, 217
- F**
- Fatigue
 - properties, 206
 - strength, 200
- Free dominant machining, *see* Free-form grinding
- Free-form grinding, 87–91
 - curve grinding sample, 91
 - experimental system, 89
 - FREEDOM grinding, 89–92
 - FREEDOM principle, 87, 88
 - FREEDOM tool, 87–88
 - FREX-DO! Tool, 88
 - grinding condition to spherical, 90
 - grinding conditions and surface roughness, 90
 - grinding state, 89
 - predressing of wheels, 89
 - problems of change in form, 87
 - spherical grinding sample, 91
 - surface roughness to spherical, 91
- FREX-DO! Tool, 88
- Fuji ELIDer, 148
- Fundamentals, 3–24
 - bonding materials, 8
 - change in stock removal in wheel diameter with truing time, 14
 - components, 4–5
 - coolant flow between electrodes, 14
 - copper tungsten, 11
 - developed principle, 3
 - effects, 5–7
 - efficient grinding with ELID, 9–10
 - efficient shape-grinding for ceramics, 10
 - electrical behavior of, 7, 18, 19
 - electrode, 3
 - electrodischarge truing, 11
 - ELID grinding technique, construction of, 4
 - experimental setup system, 16
 - experimental system, 17
 - fitted regression model, 20
 - fluids (bond oxidation kinetics), 14–23
 - discussion, 18–23
 - electrical behavior, 15–17
 - experimental results, 15–17
 - experimental system, 14–15
 - oxide layer thickness, 17
 - grinding force for ceramics, 9
 - grinding with superfine abrasives, 10
 - ground surface quality, 5
 - hydroxides, 7
 - ion transportation, 18
 - machine setup with electrodischarge truer, 12
 - mathematical model, wheel topography, 11
 - mechanism, 7–9
 - metal-bond sample, 17
 - microplasma truing device, 12
 - mirror surface quality grinding, 6
 - nanoprecision surface finishing, 10
 - nonlinear regression model, 23
 - power supply, 5, 14
 - principle of ELID system, 15
 - principle of microplasma discharge truing, 12

relationships between grain size and surface roughness, 6, 11
response surface gap, 21
response surface voltage, 22
schematic of ELI-grinding, 4
sharply trued grinding wheel edge, 13
stability of grinding force, 6
theory math model, 23
thickness change velocity of flow, 20
truing for ELID grinding, 10–14
wheel surface after grinding with ELID, 9
wheel surface electroconductivity, 7

G

GD-OES, *see* Glow discharge optical emission spectroscopy

Glow discharge optical emission spectroscopy (GD-OES), 203

Grinding applications, 123–235

adhesiveness to thin films, 208

AFM image, 132

AFM principle, 157

Al-series specimens, 202

aluminum binding energy, 204

aluminum fluoride, 208

analysis of abrasive elements, 203

analysis of oxygen element, 203

analyzers used in study, 203

anodic oxidation reaction, 218

anticorrosion film, 200

basic ELID rotary grinding machine with cup-type wheel, 125

basic grinding test conditions and results, 128

cell number, 222

change of oxygen atom concentration by difference in additional potential, 214

charging of diamond abrasives, 149

chemical stability of surface, 218

chemical vapor deposition, 132

comparison of compressive residual stress, 205

comparison of corrosion potential, 219

comparison of microcutting mark of generated surface, 191

comparison of optical roughness map of generated surface, 195

comparison of polarization resistance, 220

comparison of surface roughness obtained using ELID polishing and conventional

concentrations of dissolved oxygen, 202

concept of surface and interface functional modification, 200

corrosion rate test, 207

corrosion resistance

evaluation, 207

passive state, 221

crystallographic planes, 139

C-series specimens, 202

cutting condition, 180

cyclic polarization curves, 220

deflection measurement result, 179

desktop cylindrical grinding machine, 170

detected elements profile in depth direction analyzed by using XPS, 226

diamond abrasives, 124

diamond-like carbon, 208

dissolved oxygen, 226

EDX patterns of surface, 212

effect of applied pressure on continuity of removal rate, 131

effect of cutting speed on Ra, 152

effect of depth of cut on Ra, 232

effect of ELID on continuity of removal rate, 131

effect of feed rate on Ra, 232

effect of truing time on surface roughness, 152

effect of wheel speed on Ra, 232

electrical resistivity of wheel developed, 154

electrode used for ELID polishing, 143

electrodischarge truing, 151

ELID grinding conditions, 189

ELID grinding conditions of fused silica glass, 197

ELID grinding for large-scale Si wafer, 127

ELID grinding machine with straight-type wheel, 127

ELID ground Si wafer, 126

energy-dispersive x-ray diffraction system, 217

estimated response surface, 234, 235

evaluation of biocompatibility, 226

evaluation of mechanical properties, 205

example of obtained mirror-surface finish, 131, 136

experimental conditions, 147, 169, 202, 224

experimental setup for ELID polishing, 142

experimental system specification, 230

external view of grinding machine employed for microtool machining, 168

external view of workpiece after #1200 grinding, 141

factors improving biocompatibility, 228

fatigue properties, 206

fatigue strength, 200

figure map of surface, 192

finished surface microphotographs, 224

fixture for ELID polishing, 144

form accuracy, 190

- form map of surface before and after MRF, 193
- F-test, 161, 162
- Fuji ELIDer, 148
- generation of oxide layer on ELID ground surface, 213
- glow discharge optical emission spectroscopy, 203
- grain size, 151
- ground Co-Cr alloy for artificial joint, 225
- hardness of top surface layer, 205
- hexagonal microtool, 182
- hydroxide ion, 226
- image of grinding wheel surface after stable grinding process, 125
- installed image analysis profilometer, 177
- insulator, 145
- lactate dehydrogenase, 222, 223
- large-scale ultraprecision ELID rotary grinding machine, 129
- macro-observations, 207
- material removal and current, 155
- material removal and ELID, 157
- material removal rate, 162
- material removal and voltage, 156
- measured results of corner-edge radius, 174
- measurement picture of deflection, 176
- mechanical properties of surface, 221
- metallic biomaterials, surface modification, 211–218
 - surface modification on Co-Cr alloy, 223–228
 - surface modification on titanium alloy, 211–222
- metal-resinoid hybrid bonded diamond wheel, 129, 132
- microlens mold grinding, 163
- microphotographs of ground surfaces and edges, 169
- micropin processing conditions, 171
- microtool(s), 164–181
 - deflection of, 179
 - examples of microtools fabricated by ELID grinding, 181
 - fabrication by ELID grinding, 168–172
 - generation with high-quality surfaces, 172–175
 - grinding result, 169
 - new desktop microtool machining system, development of, 175–181
 - rupture strength evaluation system, 174
 - shape accuracy, 177
 - surface roughness, 173
- Model F-value, 233
- molds, 162–164
- mounting of parts, 150
- MRF conditions, 199
 - MRF conditions of BK glass, 187
 - MRF conditions of SiC plane, 188
 - MRF removal function on BK7 after 2 seconds, 186
- Nano hardness tester, 201
- nanindentation testing, 203
- next-generation semiconductors, 138
- number of adherent cells, 228
- on-machine measurement picture, 178
- optical roughness map of surface after taking spots, 188
- optical roughness map of surface before and after MRF, 194, 196
- optics finishing integrating ELID grinding and MRF, 181–200
 - finishing characteristics, 187–198
 - form accuracy of ELID and MRF, 189–193
 - microsurface roughness of ELID and MRF, 193–198
 - removal rate of BK7 glass, 186
 - removal rate of different materials by MRF, 186–187
 - removal rate of SiC, 186–187
 - removal rate of silicon mirror, 187
- overviews of produced microtools, 182–183
- pin-on-disc tester, 206
- plasma discharge truing of wheel, 162
- polishing and grinding of magnetic heads, 142–162
 - cutting speed, 151
 - ELID parameters, 150–155
 - ELID polishing results, 155–160
 - experimental setup, 142–150
 - grain size or mesh number of wheel, 150
 - grinding force, 151–154
 - results and discussions, 155–162
 - statistical analysis, 160–162
 - truing time, 151
 - wheel material, 154–155
 - wheel resistivity, 154
- polygonal microtools, 172
 - power devices, 138
 - breakdown voltage, 139
 - performance of, 138
 - power conversion efficiency, 138
 - practically used ELID grinding machine for Si wafer, 127
- P-series procedure, 202, 203
- relation between grain size and surface roughness, 133
- relation between working time and surface roughness, 137
- relationship between surface roughness and rupture strength, 175
- residual stress measurements, 205
- results of colored surface observation, 216

- results of milling and punching test, 184
 - results of nanoindentation test, 205, 221, 225
 - results of scratch tests, 209
 - results of sliding friction test, 206, 221
 - results of wettability tests, 209
 - roughness patterns, 165, 166
 - rupture strength testing, 175
 - sapphire (experimental approach), 229–235
 - chip thickness model, 230–231
 - experimental setup, 229–230
 - results and discussion, 231–235
 - schematic showing position of fixture, 146
 - semiconductors, 124–142
 - efficient and smooth grinding
 - characteristics of monocrystalline 4H-SiC wafer, 138–142
 - ELID grinding systems of silicon wafers, 124–128
 - ELID lapping of CVD-SiC, 132–138
 - ELID lapping of monocrystalline silicon, 129–132
 - setup for electrically conductive brush, 147
 - silicon wafers, 124
 - Si-series specimens, 202
 - S-N diagram, 206
 - specifications of ELID grinding machine for semiconductor wafer, 126
 - stability of grinding performance on ELID
 - single-side lap grinding, 136
 - staged micropin, 171
 - stainless steels, surface modification, 201–211
 - analysis of mirror-finished surfaces, 203–205
 - proposed modification technique and experimental procedures, 201–202
 - surface functionality evaluation, 205–211
 - subsurface damage, 124, 126
 - supporting rollers and springs, 144
 - surface modification, 200–228
 - layer, 214
 - metallic biomaterials, 211–218
 - stainless steels, 201–211
 - surface potentials showing with contact angle, 210
 - surface profile obtained by varying current, 158
 - surface quality differences, 164, 166
 - surface roughness, 125, 203
 - surface roughness after #1200 grinding, 141
 - surface roughness before grinding, 140
 - surface roughness and current, 158
 - surface roughness of finished Co-Cr alloy, 223
 - surface roughness obtained by varying current, 159
 - surface roughness of plate after facing, 149
 - target size and size accuracy, 178
 - TEM observation of oxide layer, 212
 - titanium and oxygen profile, 218
 - tool and workpiece setup on compact desktop-type four-axis grinding machine, 224
 - transmission electron microscopy, 218
 - tribological properties, 206
 - t-test, 161, 162
 - uniform truing, 162
 - vacuum chuck table, 124
 - variation of grinding force with MRR in conventional grinding, 152
 - variation of grinding force with MRR in ELID, 153
 - variation of MRR in MRB and CIFB wheels, 154
 - view of ground mold sample, 167
 - wettability evaluation, 209
 - wheel surface after truing, 163
 - XPS analysis, 209
 - XPS depth profile of carbon, 215
 - XPS results for analysis of nitrogen, 227
 - x-ray photoelectron spectroscopy, 203
- Grinding methods, 37–60
- acoustic emission monitoring, 50–58
 - effect of depth of cut on surface finish and AE signals, 55–58
 - effect of electrolytic dressing current on AE signals, 55
 - effect of electrolytic dressing current on surface finish, 54–55
 - experimental setup, 51–52
 - predressing and oxide layer thickness, 52–54
 - results and discussion, 52–58
 - after electrolytic dressing, 40
 - anode effect, 52
 - average surface roughness, 54
 - ball-nose wheels, 45, 46
 - cast-iron bonded grinding wheel, 53
 - chip thickness model, 54
 - copper electrode, 51
 - developed machine for microtool machining, 39
 - ductile-mode grinding, 57
 - electroconductive grinding liquid, 39
 - electrodeless ELID, 43–46
 - electrolytic dressing current, 53, 54, 55
 - ELID II method, 42
 - ELID III method, 43, 44
 - ELID IV grinding system, 47
 - experimental conditions, 40, 48
 - experimental system, 44
 - grinding scene, 48
 - grinding wheel topography, 51
 - interval dressing, 43

- interval ELID, 42–43
 - ion-shot ELID, 47–49
 - lapping machine
 - grinding conditions by, 44
 - view of, 45
 - lens glass mold, 49
 - microlens mold fabrication, 42
 - minimum quantity lubrication, 37
 - mist ELID, 37–41
 - nozzle ELID method, 47
 - oxide layer thickness, 53
 - piezoelectric type transducer, 51
 - plasma discharge truing system, 39
 - preamplifier, 51
 - relation between electrolysis film thickness and mist supply, 41
 - relation between electrolysis film thickness and whetstone rotation speed, 41
 - sapphire, 50
 - semidry ELID method, 38
 - surface roughness, 46
 - TRIDER-X grinding machine, 47
 - yellow-brown oxide layer formed on cast-iron bonded wheel surface, 53
 - Grinding types, fundamental, 25–33, *see also*
 - Lap grinding
 - aspheric grinding, 32
 - centerless grinding, 29, 30
 - center-type grinding, 28
 - curve generator grinding, 29–31
 - cylindrical grinder, 28, 29
 - ELID electrodes, 25
 - experimental setup, 31
 - in-feed grinding systems, 25, 28
 - in-process dressing, 29
 - internal grinding, 28–29
 - rotary grinding system, 27
 - surface grinding, 25, 26
 - Ground surface quality, 5
- H**
- Hard disk drive (HDD), 95
 - HDD, *see* Hard disk drive
 - HICARION, 70
 - Honing, 75–85
 - application to automobile parts, 78–84
 - application to hard and brittle material, 77–78
 - cost reduction effects, 83
 - electrical corrosion, prevention of, 78
 - electrodes, 75
 - energy-saving effects, 82
 - engine block, 78
 - honing conditions, 77
 - honing machine, 80
 - honing wheel surface, 84
 - inconsistencies in roughness values, 80
 - mass production, 79, 81, 82, 83
 - method illustration, 76
 - principle, 75
 - properties of typical ceramic materials used in ELID honing
 - results, 78
 - samples finished, 79
 - scanning electron microscope image, 83
 - setup, 76–77
 - specifications of base machine for ELID honing machine, 76
 - specifications of ELID honing experiment system, 76
 - surface roughness, 80
 - tool life, 82
 - Hydroxide
 - formation, 7
 - ion, 226
- I**
- In-process dressing, 14, 29. *see also* Electrolytic in-process dressing
 - Input-laser beam, 95
 - Insulator, 145
 - Ion transportation, 18
- L**
- Lactate dehydrogenase (LDH), 222, 223
 - Lap grinding, 61–73
 - brittle-ductile transition, 68
 - chemical-solution-type grinding fluid, 62
 - close-up view of ELID single-side lap grinding, 62
 - difference in ground surface roughness and removal rate, 64
 - double-side lap grinding, 69–72
 - ELID double-side lap grinding system, 70
 - features of HICARION, 70
 - grinding characteristics, 71
 - schematic illustration, 70
 - effects of ELID on continuity of removal rate of tungsten carbide, 63
 - example of obtained mirror surface finish, 72
 - HICARION, 70
 - metallic-bonded wheels, 69
 - monocrystalline silicon, 61, 65, 66
 - noncomplex grinding, 69
 - relation between time and stock removal, 71
 - schematic illustration of ELID single-side lap grinding, 62
 - simultaneous grinding, 66

- single-sided lap grinding, 61–69
 - effects of ELID on single-side lap grinding, 62–64
 - ELID single-side lap grinding system, 61–62
 - grinding characteristics of
 - monocrystalline silicon and tungsten carbide, 64–65
 - simultaneous grinding of different materials, 66–68
 - surface roughness profiles, 68
 - surface roughness profiles by #4000 wheel, 63
 - surface roughness profiles of tungsten carbide, 71
 - tungsten carbide, 61, 65, 66
 - view of resultant mirror surface, 67
- Lapping machine
 - grinding conditions by, 44
 - view of, 45
- LDH, *see* Lactate dehydrogenase
- Lens glass mold, 49
- M**
- Magneto-rheological finishing (MRF), ix, 185
- Magneto-rheological finishing (MRF), optics
 - finishing integrating ELID grinding, 181–200
 - finishing characteristics, 187–198
 - form accuracy of ELID and MRF, 189–193
 - microsurface roughness of ELID and MRF, 193–198
 - MRF conditions, 199
 - removal rate of BK7 glass, 186
 - removal rate of different materials by MRF, 186–187
 - removal rate of SiC, 186–187
 - removal rate of silicon mirror, 187
- Metal-resinoid hybrid bonded diamond (MRB-D) wheel, 129, 132
- Micro-ELID grinding, *see* Desktop and micro-ELID grinding
- Microplasma discharge truing, 12
- Microtools, 164–181
 - deflection of, 179
 - examples of microtools fabricated by ELID grinding, 181
 - external view of developed machine, 39
 - extremely fine, 119
 - fabrication by ELID grinding, 168–172
 - generation with high-quality surfaces, 172–175
 - grinding principle, 118, 120
 - grinding result, 119, 169
 - hexagonal, 182
 - machining examples, 120
 - new desktop microtool machining system, development of, 116, 175–181
 - polygonal, 172
 - rupture strength evaluation system, 174
 - shape accuracy, 177
 - surface roughness, 173
- Micro-workshop, 112
- Minimum quantity lubrication (MQL), 37
- Model
 - chip thickness, 54
 - fitted regression, 20
 - theory math, 23
 - wheel topography, 11
- MQL, *see* Minimum quantity lubrication
- MRB-D wheel, *see* Metal-resinoid hybrid bonded diamond wheel
- MRF, *see* Magneto-rheological finishing
- N**
- Nano hardness tester (NHT), 221
- Nanoindentation test, 205, 221, 225
- Nanoprecision grinding, *see* Ultraprecision and nanoprecision grinding
- NHT, *see* Nano hardness tester
- Nozzle ELID method, 47
- O**
- OAM recording technologies, *see* Optically assisted magnetic recording technologies
- Online process control, viii
- Optical glass, desktop slicing for, 114
- Optically assisted magnetic (OAM) recording technologies, 95
- Oxide
 - aluminum, 185
 - anodic oxidation reaction, 202
 - bonding statuses, 217
 - cerium, 185, 187
 - chromium, 225
 - copper grinding wheels, 5
 - film component, 217
 - layer
 - breakage, 58
 - corrosion resistance and, 222
 - generating process, 14
 - growth, 208
 - performance, influence on, 231
 - TEM observation, 212
 - thickness, 17
 - wear, 8
 - titanium alloy, 214
 - zirconium, 79

P

- Piezoelectric crystal, viii
- Plasma discharge truing, 162
- Power devices
 - breakdown voltage, 139
 - performance of, 138
 - power conversion efficiency, 138
- P-series procedure, 202, 203

Q

- Quasiplastic cutting, vii

R

- RMS. *see* Root mean square
- Root mean square (RMS), 185
 - acoustic emission, 50, 51, 55
 - BK7 glass sphere, 193
 - CVD-SiC, 194
 - surface microroughness, 185, 193
 - surface roughness, 102
- Rotary grinding system, 27
- Rotary index table, 116
- Rupture strength evaluation system, 174

S

- Sapphire
 - applications, 50
 - ELID grinding of, 51
 - grinding of (experimental approach), 229
 - chip thickness model, 230–231
 - experimental setup, 229–230
 - results and discussion, 231–235
 - machining of, 50
- Scanning electron microscope (SEM) image, 83, 133
- Semiconductors, 124–142
 - conductive wheels, 43
 - efficient and smooth grinding characteristics of monocrystalline 4H-SiC wafer, 138–142
 - ELID grinding systems of silicon wafers, 124–128
 - ELID lapping of CVD-SiC, 132–138
 - ELID lapping of monocrystalline silicon, 129–132
 - grinding machines specifications, 126
 - industry, ELID in, ix
 - materials microfabrications for, 112
 - microtools, 164
 - next-generation, 138
 - power conversion, 138
- SEM image, *see* Scanning electron microscope image

- SIL, *see* Solid immersion lens
- SIM, *see* Solid immersion mirror
- Si-series specimens, 202
- Sliding friction test, 206, 221
- Solid immersion lens (SIL), 95
- Solid immersion mirror (SIM), 95, 97

T

- TEM, *see* Transmission electron microscopy
- Theory, nonlinear regression, 23
- Transducer, piezoelectric, viii, 51
- Transient elastic wave (lattice of crystalline materials), release of, viii
- Transmission electron microscopy (TEM), 212, 218
- Tribological properties, 206
- TRIDER-X grinding machine, 47

U

- Ultrahard materials, vii
- Ultraprecision and nanoprecision grinding, 95–109
 - atomic force microscopy, 98
 - cast iron–cobalt hybrid wheels, 106
 - condense result, 100
 - construction four-axes ultraprecision machine tool, 96
 - double hydrostatic guideway, 104
 - ELID grinding conditions, 106
 - experimental conditions, 98, 102
 - form error of grinding wheel, 103
 - four-axis ultraprecision machine, 101
 - ground profile, 102
 - hard disk drive, 95
 - hemiparaboloidal SIM, 97
 - input-laser beam, 95
 - large optics produced by ELID, 107–108
 - large-scale ultraprecision and nanoprecision grinding, 103–108
 - on-machine metrology profile probe, 102
 - optically assisted magnetic recording technologies, 95
 - paraboloidal lens processing, 102
 - paraboloidal surface, 95
 - power supply, 106
 - profile accuracy, 97
 - SIM after processing, 99
 - single-point diamond cutting, 96
 - solid immersion lens, 95, 96
 - solid immersion mirror, 95, 96
 - specifications of developed grinding system, 105
 - specifications of four-axes ultrahigh precision machine tool, 101
 - specifications of ultraprecision machine tool, 97

- state of paraboloidal lens processing, 102
- step response of Z-axis movement, 104
- straightness of workpiece, 107
- surface roughness, 99, 103
- tool path, 98
- ultraprecision grinding of glass-ceramic mirror, 100–102
- ultraprecision grinding of solid immersion mirror, 95–100
- ultraprecision mirror surface machining system with ELID, 104
- ultraprecision pneumatic spindle, 97
- Z-axis movement, 103
- Zerodur glass-ceramic material, 100, 101

V

Vacuum chuck table, 124

W

Wettability evaluation, 209

Wheel(s)

- ball-nose, 45, 46
- cup-type, 125
- electrical resistivity, 154
- material, 154–155
- metallic-bonded wheels, 69

- metal-resinoid hybrid bonded diamond, 129, 132
- plasma discharge truing of wheel, 162
- predressing of, 89
- surface after grinding with ELID, 9
- surface after truing, 163
- surface electroconductivity, 7
- topography, 11

X

XPS, *see* X-ray photoelectron spectroscopy

X-ray photoelectron spectroscopy (XPS), 203

- Co-Cr alloy surface examination, 225

- depth profile of carbon, 215

- detected elements profile in depth direction analyzed, 226

- results for analysis of aluminum, 204

- results for analysis of nitrogen, 227

- results for analysis of titanium and oxygen in the 90 V series, 218

- results of measuring elemental Fe, Cr, and O, 208

Z

Z-axis movement, 103

Zerodur glass-ceramic material, 100, 101